

WDR Full Body Camera

FEATURES

Superior Images even in Tough Back Light Condition
 Wide Dynamic Range: 95dB(14Bit), 120dB Max.
 Automatic 5 Level Exposure Control for each Pixel
 Good Smearless even in the Presence of Strong Light
 On Screen Menu and Camera ID
 DC12V/AC24V Dual Power (Non-Polarity)



GPX-F704DS

SPECIFICATIONS

Model	GPX-F704DS
Image Sensor	Pixim 1/3" Digital Pixel System Technologies [D1500R]
TV System	NTSC / PAL Selectable
Effective Pixels	410K
Horizontal Resolution	540TVL
Scanning System	Progressive Image Capture
Sync. System	Internal(DC12V)/L.L(External/AC24V) : Auto Switching
Min. Illumination	0.6 Lux
Lens	C/CS Mountable (Not Included)
Electrical Shutter	1/60 ~ 100,000(NTSC), 1/50 ~ 100,000(PAL)
S/N Ratio	More than 50dB (AGC Off)
Video Output	VBS 1.0Vp-p Composite
OSD Control	
	Video Setup: TV System, SYNC, SYNC Auto Sense
Camera Setup	Lens Selection: Lens Type, DC Gain, Video Gain, AI Thresh
	Video Adjustment: White Balance, AGC, BLC, FLK, Gamma, Resolution, Sharpness, Saturation
WDR Setup	Auto, Low, High, Manual
Display Setup	Camera Title, Mirror, Low Light
Electrical	
Power Source	DC12V/AC24V Dual Power (Non-Polarity)
Power Consumption	DC12V : 250mA / AC24V : 5W
Video Output Connector	BNC
Power Output Connector	Terminal Block
Environmental	
Operating Temperature	14°F ~ 122°F (-10°C ~ 50°C)
Storage Temperature	-22°F ~ 140°F (-30°C ~ 60°C)
Operating Humidity	Up to 90%RH
Mechanical	
Camera Mount	1/4"-20UNC thread on top and bottom
Material	Aluminum
Color	Ivory
Dimensions(mm)	65(W)X54(H)X133(D)
Weight	300g